

UNIVERSITY OF CALCUTTA

OFFICE OF THE UNIVERSITY ENGINEER 87/1, College Street Darbhanga Building, GroundFloor Kolkata-700073 Website :-www.caluniv.ac.in

NOTICE INVITINGQUOTATION

University of Calcutta invites sealed tender from resourceful and bonafide contractors for the following work				
1.	N.I.T. No:	Eng /CT- 63/22-23 Date: 25.04.2022		
2.	Name of the month	Renovation of Room no-ES-114 to a Seminar Room for the Department of Electronics		
	Name of the work:	Science at Hostel Bldg. Of Rajabazar Sc. College.		
3.	Estimated Cost put to Tender:	Rs. 457579.69 (Including G.S.T)		
4.	Earnest Money:	A sum of 2% of the quoted amount in the form of CTS demand draft in favour of University of Calcutta payable at Kolkata is to be attached with the Tender as earnest money failing which the tender will be treated cancelled. The earnest money will be returned to unsuccessful tenders on application after issuing of work order to the successful bidder. In case of successful tender the EMD will be returned on application after an equal amount of security deposit is ducted by the University from the running bills. EMD is not exempted in any case.		
5.	Time of completion:	45days		
6.	Eligibility Criteria and Documents to be submitted along with Application.	Valid trade License, GST & PAN and credential for satisfactory completion of similar nature of job amounting75 % of the estimated value in a single tender in the last three financial years in Government /Government Undertaking or University of Calcutta. Original documents may be asked for verification of technical checking on the date of issuing tender paper. Failing to produce original documents, the tender will be rejected. The participant bidder must submit the following documents in sealed envelope in the tender box kept at the Office of the Engineer at the Ground Floor of the Darbhanga Building, University of Calcutta, 87/1, College Street, Kolkata – 700073 within the last date of submission of the tender. 1. NIT documents duly filled and signed by the intending bidder. 2. Bank Draft for EMD in favour of the University of Calcutta. 3. Self-attested copy of Valid trade License, GST & Pan and credentials for satisfactory completion of similar nature of jobs under Government, Government Undertaking and Universities etc. within last three years. 4. Application through postal service or courier service is not accepted.		
7.	Last date of receipt of application for tender	On 27/04/2022 from 11AM to 4 PM (Must contain above mentioned document. The application duly signed by Engineer CU should be enclosed with tender documents.		
8.	Last date of issue of tender papers	TO BE DOWNLOADED FROM WEBSITE.(www. caluniv.ac.in)		
9.	Last Date and Time of tender Submission	Dully filled and signed tender/quotation to be submitted on 05 / 05/ 2022 from 11am to 2.00 PM in to the Tender Box kept in the Office of the University Engineer		
10.	Date and Time of Tender Opening	At or after 05 / 05/ 2022 after 3 pm at the Office of the University Engineer. Intending bidders are requested to be present at the time of opening tenders/quotations.		

N.I.T no : Name of work and the date of opening should be written on the sealed envelope otherwise tender will not be opened and will be rejected.

The undersigned reserves the right to reject any or all Tenders without assigning any reason what so ever.



UNIVERSITY ENGINEER (C.U)



UNIVERSITY OF CALCUTTA

Name of the work:- <u>Renovation of Room no-ES-114 to a Seminar Room for the Department of Electronics</u> <u>Science at Hostel Bldg. Of Rajabazar Sc. College.</u>

N. I.T. no- Eng /CT- 63/22-23 Date: 25.04.2022
Estimated cost Put to Tender:- Rs. 457579.69 (Including G.S.T)
Name of Agency:-
Address of Agency:-
Rate quoted by Agency:(in figure and words)
Signature of the Agency with date &stamp:-



UNIVERSITY OF CALCUTTA

N. I.T. no : Eng /CT- 63/22-23 Date: 25.04.2022

GENERAL TERMS AND CONDITION

- 1. Eligible Tenders will have to download the tender papers from the website & drop the filled tender papers signed with seal and date at every page along with copy of Valid Trade license's, GST & PAN and Credential for satisfactory completion of similar nature of job amounting to at least seventy five percent of the job value in a single tender from any Government, Govt. undertaking or University of Calcutta in the last three financial yearin sealed envelope in the Tender box kept in the Office of the undersigned with in the specified time mentioned in the NITwhich will be opened by the undersigned or by his representative with in the tendered must write the name of the work, NIT no, the date of opening and name of the bidder on the envelop failing which the tender will not be opened thus will be treated as cancelled.
- **2.** The rate should be quoted after inspection of the site and inclusive of all incidental charges i.e. freight, insurances, labour insurances, handling charges, necessary government taxes, duties etc as well as the Water, Electricity charges which are to be paid as per rules .
- **3**. The contractor shall be responsible to ensure compliance with the provision of minimum wages act 1948 as modified up to date and the rules made in respect of any employees, employed by the contractor directly or through the petty or subcontractor for the purpose of carrying this contract. The contractor shall be responsible for any damage, injury or loss caused by the work or workmen to any person, animal or material during the progress of work.
- **4.** Liquidated damage will be charged to the contractor if they fail to complete the work within the stipulated time, 0.01% per day to a maxi mumli mit of 10% of the contract value.



5. The allotted time for completion of the work as specified in the NIT from the date of receipt of work order .Time is the essence of this contract. Normally no time extension will be granted. In case of prayer for extension of time the University authority has the full right reserved to grant it or discard it.

6.If the successful contractor's bid rate is 80% or less than the estimated amount put to tender the contractor will have to submit a Bank Guarantee amounting to 10% of the Tendered amount before issue of Work order failing which the EMD will be forfeited and the agency may be blacklisted. The Bank Guarantee should be valid till the end of the contract period and shall be renewed accordingly if required. This bank Guarantee is an Additional Performance Security .So provision of deducting Security deposit from bills will hold goods per relevant clause of the contract. The bank Gurrantee shall be returned immediately on successful completion of contract.

(b) The University authority will retain a sum amounting to 10% of the bill of the contract for a period of six months from the date of completion of work as **Security Deposit**. Which will be released after a period of six months from the date of completion of the work on application.

7. A sum of 2% of the quoted amount in the form of CTS demand draft in favour of University of Calcutta payable at Kolkata is to be attached with the Tender as earnest money failing which the tender will be treated cancelled. The earnest money will be returned to unsuccessful tenders on application after issuing of work order to the successful bidder. In case of successful tender the EMD will be returned on application after an equal amount of security deposit is ducted by the University from the running bills. EMD is not exempted in any case. The earnest money will be returned to unsuccessful tenderers on application after issue of work order to the successful bidder for successful tenderer the EMD will be returned on application after an equal amount of security deposit is deducted from the running bills.

Amount:-Rs			
D.D No	Dated	/	/20
Name of Issuing Bank:			
Branch :-			

8. Work is to be carried out as per specification laid in the B.O.Q or PWD specification as per instruction of the University Engineer or his representative.



- **9.**The materials brought to site for execution of the work should by no means be taken out of site without the permission of the Engineer C.U.
- **10.** The rates must be quoted in words in figure otherwise the tender will be cancelled.
- 11. The University will not be bound to accept the lowest bidder.
- **12**. The University will not supply any materials to the contractor.
- **13**. The contractor will work under the strict supervision of the Engineer/ Sub-Assistant Engineer. The estimate given along with the tender are provisional payment will be made on the actual work done jointly measured by the Engineer or his representative (Sub-Assistant- Engineer) & the contractor or his representative. The contractor will have to submit bill in printed format in duplicate.
- **14.** The contractor will have to take necessary instruction from the Engineer CU/ Sub-Assistant Engineer regarding the execution of work.

15. Defect & liability Period: The defect & liability period will be for a period of six months from the date of completion of the job. Any defects pointed out during this period has to be mend good by the agency at their own cost failing which the retention money will be for feited.

Sd/-

University Engineer

Name of the Agency:

Address:-

Signature of the Agency with date &stamp:-

<u>SPECIFIC PRICE SCHEDULE for Renovation of Room no-ES-114 to a Seminar Room for the Department of Electronics Science at Hostel Bldg. Of Rajabazar Sc. College.</u>

SL.NO <u>.</u>	DESCRIPTION OF ITEM.	UNIT <u>.</u>	QUANTITY.	RATE.	AMOUNT.
1. (page45 Item8b).	Applying 2 coats of Non-Toxic Acrylic Polymer modified Paint having adhesive & waterproofing properties by mixing in proportion (1 liquid: 4 cementitious material) or as per manufacturer's specification for water proofing layer.	Sqm.	5.00	RS. P. 258.00	RS. P.
2. (page233 Item1)	Supplying profiles of required section made of Aluminium Alloy Extrusions conforming to IS: 732-1983 and IS: 1285- 1975; Annodized (with required film thickness and specified colour / natural) matt finished conforming to IS: 1868-1983 for fabrication of composit door, sliding & casement windows, partitions, formed of basic sections of any ISI embossed / certified make and brand as per direction of Engineer – InCharge. Fixed glazing. i) Top, bottom and side member. 2x3x1.8=10.8 2x1.4=2.8 2x1.2=2.4 2x3x1.5=9.0 2x2.0=4.0 2x1.4=2.8 ii)mullion- 3x1.5=4.5 1x2.0=2.0 1x1.4=1.4 3x1.5=4.5 1x2.0=2.0 1x1.4=1.4 iii) glazing clip. 2x4x3x2(0.9+0.75)=79.2 2x4x2(1.0+0.7)=27.2	Rmt.	32.00 16.00	321.00 339.00 50.00	10272.00 5424.00 6200.00
3.	2x4x2(0.7+0.6)=16.6 Labour charge for fabrication and				

(page239 Item2).	installation of composite door, window, partitions made from annodized extruded alloy aluminium sections for the following units:- Fixed glazing. 3x1.5x1.8=8.1 1x2.0x1.4=2.8 1.4x1.2x1=1.68	Sqm.	14.00	768.00	10752.00
4. (page243	Supplying bubble free float glass of approved make and brand				
Item9).	conforming to IS: 2835-1987. 5 mm thick 3x4x0.85x0.7=7.14 4x0.95x0.65=2.47	Sqm.	14.00	585.00	8190.00
	4x0.65x0.55=1.43				
5. (page158 Item3A).	Providing and fixing of false ceiling with powder coated exposed G.I. grid suspension system (E-Grid T 2430 or equivalent load carrying capacity with mid span deflection not exceeding 1/360 span with hanger spacing of 1200mm c/c) consisting of Main Runner 3600 mm long, Cross Tee 1200 mm / 600 mm long and Wall Angle. The Wall Angle shall be fixed on PVC Dash Fasteners on the perimeter of the wall by steel screws with distance 300mm c/c. The Main Runners to be placed @ 1200 mm. The Cross Tee 1200mm will be inserted in the pre-cut slots of Main Runner at a regular interval of 600 mm to form a modular grid of 1200mm X 600mm. Additional Cross Tees of 600 mm shall be placed perpendicular to the Cross Tee 1200 mm long to finally form a grid of 600 mm X 600 mm. Grid of module size 600 mm X 600 mm. Grid of module size 600 mm X 600 mm shall be supported by 6 mm dia G.I. wire from purlins / soffit. 6 mm thick High Pressure				
	Steam Cured Non Asbestos Fibre Cement Standard Ceiling Board (Density > 1300 Kg/m3) of size 595 mm X 595 mm, conforming IS 14862 & Type B Category III of ISO 8336,				
	tested as per AS-1530 part 3 & BS-476 Part 4,5,6,7 & 8, should be placed in the Grid module to form a False Ceiling. All complete as per the drawing & directions of Engineer-in-				
	charge. 8x5.5=44.00	Sqm.	50.00	686.00	34300.00

6.	Wood work in door and window frame fitted and fixed in position				
(page114 Item1).	complete including a protective coat				
itteriii).	of painting at the contact surface of				
	the frame exluding cost of concrete,				
	Iron Butt Hinges and M.S clamps.				
	(The quantum should be correted				
	upto three decimals).	Cum.	0.3	83218.00	24965.40
7.					
(page177	Supplying and fitting in all places of				
Item12).	wall panelling to all heights and fixing				
	on pre- framed existing frame work				
	grid with glass wool of 50mm thick having density of 48 Kg per cum. to				
	be inserted into the pre - fabricated				
	slot covered the glass wool by				
	marking cloths treated with Naptha				
	@ 0.07 Ltr.per Sq.m. of cloths. Finally				
	12.5mm thick gypsum Fulton board				
	having size 595mmX595mm fitted &				
	fixed into the pre-fabricated grid and				
	covered the all perifirial gaps of				
	fulton board by self additive fibre				
	tape with necessary filler if required,				
	complete in all respect as per direction of the Engineer-in-charge.				
	2x(8.0+5.0)x3.2=83.2	Sqm.	90.00	1182.00	106380.00
8.	Applying Interior grade Acrylic Primer				
(page195	of approved quality and brand on				
Item7).	plastered or concrete surface old or				
10011177.	new surface to receive Distemper/				
	Acrylic emulsion paint including				
	scraping and preparing the surface				
	throughly, complete as per				
	manufacturer's specification and as				
	per direction of the EIC.				
	2x(8.0+5.0)x4=104 8x5=40	Sqm.	150.00	33.70	5055.00
9.	Acrylic Distemper to interior wall,	5 4		00.70	0000100
(page196	ceiling with a coat of solvent based				
Item10).	interior grade acrylic primer (as per				
	manufacturer's specification)				
	including cleaning and smoothning of	Sqm.	150.00	70.00	10500.00
	surface.	1-11-			
	10. Priming one coat on timber or plastered surface with synthetic oil				
Item1b).	bound primer of approved quality including smoothening surfaces by				
	sand papering etc.		222.62	20.00	0740.00
	90x2+40	Sqm.	230.00	38.00	8740.00
11. (page200	Painting with best quality synthetic enamel paint of approved make and				

tem2). brand including smoothening surface by sand papering etc. including using of approved putty etc. on the surface, if necessary: 12. Dismantling all types of plain cement concrete works, stacking serviceable materials at site and removing rubbish as directed within a lead of 75 m. In ground floor including roof 13. Supplying and laying true to line and (size not less than 600 mm X 10 mm thick) in floor, skirting etc. Set in 20 mm sand cement mortar (1.4) and 2 mm thick cement slurry back side of tiles using cement @ 2.91kg./sq/M or using polymerised adhesive (6 mm thick layer applied directly over finished artificial stone floor/Mosaic etc without any backing course) laid after application slurry using 1.75 kg of cement per saM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1.4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m, white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete ltem4).	Itoma 2\	hrand including smoothaning surface				
of approved putty etc. on the surface, if necessary: 12. Dismatling all types of plain cement concrete works, stacking serviceable materials at site and removing rubbish as directed within a lead of 75 m. In ground floor including roof 13. Supplying and laying true to line and (p-66 level vitrified tiles of approved brand (size not less than 600 mm X 600 mm X 10 mm thick) in floor, skirting etc. Set in 20 mm sand cement mortar (1:4) and 2 mm thick cement slurry back side of tiles using cement @ 2.91kg,/salf or using polymerised adhesive (6 mm thick layer applied directly over finished artificial stone floor/Mosaic etc without any backing course) laid after application slurry using 1.75 kg of cement per sqM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/Sq.m, white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete	Item2).	_				
12. Dismantling all types of plain cement concrete works, stacking serviceable materials at site and removing rubbish as directed within a lead of 75 m. In ground floor including roof 55 m. In ground floor including roof 55 m. In ground floor including roof roof roof roof roof roof roof roo						
12. Dismantling all types of plain cement concrete works, stacking serviceable materials at site and removing rubbish as directed within a lead of 75 m. In ground floor including roof 13. Supplying and laying true to line and level vitrified tiles of approved brand (size not less than 600 mm X 600 mm X 10 mm thick) in floor, skirting etc. Set in 20 mm sand cement mortar (1.4) and 2 mm thick cement slurry back side of tiles using cement @ 2.91Kg,/sqM or using polymerised adhesive (6 mm thick layer applied directly over finished artificial stone floor/Mosaic etc without any backing course) laid after application slurry using 1.75 Kg of cement per sqM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/Sq.m, white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete (1.2) and the ceme			Sqm.	230.00	79.00	18170.00
concrete works, stacking serviceable materials at site and removing rubbish as directed within a lead of 75 m. In ground floor including roof 13.	_	·				
materials at site and removing rubbish as directed within a lead of 75 m. In ground floor including roof 13.	12.	,, ,				
rubbish as directed within a lead of 75 m. In ground floor including roof 13. (p-66 ii-36) Supplying and laying true to line and level vitrified tiles of approved brand (size not less than 600 mm X 600 mm X 10 mm thick) in floor, skirting etc. Set in 20 mm sand cement mortar (1:4) and 2 mm thick cement slurry back side of tiles using cement @ 2.9.1Kg./sqlM or using polymerised adhesive (6 mm thick layer applied directly over finished artificial stone floor/Mosaic etc without any backing course) laid after application slurry using 1.75 kg of cement per sqlM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the control With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. (page76 Artificial stone in floor, dado, staircase etc with cement concrete		_				
75 m. In ground floor including roof 13. (p-66 i-36) Supplying and laying true to line and level vitrified tiles of approved brand (size not less than 600 mm X 600 mm X 10 mm thick) in floor, skirting etc. Set in 20 mm sand cement mortar (1:4) and 2 mm thick cement slurry back side of tiles using cement @ 2.91kg./sqM or using polymerised adhesive (6 mm thick layer applied directly over finished artificial stone floor/Mosaic etc without any backing course) laid after application slurry using 1.75 kg of cement per sqM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the control) With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m, white cement for joint filling with pigment. Deep Colour & White 14. (page76 Artificial stone in floor, dado, staircase etc with cement concrete						
13. (p-66 i-36) Supplying and laying true to line and level vitrified tiles of approved brand (size not less than 600 mm X 600 mm X 10 mm thick) in floor, skirting etc. Set in 20 mm sand cement mortar (1:4) and 2 mm thick cement slurry back side of tiles using cement @ 2.91kg./sqM or using polymerised adhesive (6 mm thick layer applied directly over finished artificial stone floor/Mosaic etc without any backing course) laid after application slurry using 1.75 kg of cement per sqM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete						
13. (p-66 i-36) (p-66 i-36) (p-66 i-36) (size not less than 600 mm X 600 mm X 10 mm thick) in floor, skirting etc. Set in 20 mm sand cement mortar (1:4) and 2 mm thick cement slurry back side of tiles using cement @ 2.91Kg./sqM or using polymerised adhesive (6 mm thick layer applied directly over finished artificial stone floor/Mosaic etc without any backing course) laid after application slurry using 1.75 Kg of cement per sqM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete		75 m. In ground floor including roof	Cum.	2.0	1417.00	2834.00
(p-66 i-36) level vitrified tiles of approved brand (size not less than 600 mm X 600 mm X 10 mm thick) in floor, skirting etc. Set in 20 mm sand cement mortar (1:4) and 2 mm thick cement slurry back side of tiles using cement @ 2.91Kg./sqM or using polymerised adhesive (6 mm thick layer applied directly over finished artificial stone floor/Mosaic etc without any backing course) laid after application slurry using 1.75 Kg of cement per sqM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete	12	Supplying and laying true to line and	- CG1111	2.0	1117.00	20000
(size not less than 600 mm X 600 mm X 10 mm thick) in floor, skirting etc. Set in 20 mm sand cement mortar (1.4) and 2 mm thick cement slurry back side of tiles using cement @ 2.91Kg,/sqM or using polymerised adhesive (6 mm thick layer applied directly over finished artificial stone floor/Mosaic etc without any backing course) laid after application slurry using 1.75 Kg of cement per sqM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1.4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint fillling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete						
X 10 mm thick) in floor, skirting etc. Set in 20 mm sand cement mortar (1:4) and 2 mm thick cement slurry back side of tiles using cement @ 2.91kg./sqM or using polymerised adhesive (6 mm thick layer applied directly over finished artificial stone floor/Mosaic etc without any backing course) laid after application slurry using 1.75 kg of cement per sqM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete						
Set in 20 mm sand cement mortar (1:4) and 2 mm thick cement slurry back side of tiles using cement @ 2.91Kg,/sqM or using polymerised adhesive (6 mm thick layer applied directly over finished artificial stone floor/Mosaic etc without any backing course) laid after application slurry using 1.75 Kg of cement per sqM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete	1-36)					
(1:4) and 2 mm thick cement slurry back side of tiles using cement @ 2.91kg./sqM or using polymerised adhesive (6 mm thick layer applied directly over finished artificial stone floor/Mosaic etc without any backing course) laid after application slurry using 1.75 kg of cement per sqM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete		·				
back side of tiles using cement @ 2.91kg./sqM or using polymerised adhesive (6 mm thick layer applied directly over finished artificial stone floor/Mosaic etc without any backing course) laid after application slurry using 1.75 kg of cement per sqM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete						
2.91Kg./sqM or using polymerised adhesive (6 mm thick layer applied directly over finished artificial stone floor/Mosaic etc without any backing course) laid after application slurry using 1.75 Kg of cement per sqM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete		,				
adhesive (6 mm thick layer applied directly over finished artificial stone floor/Mosaic etc without any backing course) laid after application slurry using 1.75 kg of cement per sqM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/Sq.m, white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete		•				
directly over finished artificial stone floor/Mosaic etc without any backing course) laid after application slurry using 1.75 Kg of cement per sqM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. (page76 staircase etc with cement concrete						
floor/Mosaic etc without any backing course) laid after application slurry using 1.75 Kg of cement per sqM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete (1.2 d. Whith the table with respect to the control concrete)						
course) laid after application slurry using 1.75 Kg of cement per sqM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete (1-2) which the state where the state is considered.		*				
using 1.75 Kg of cement per sqM below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete		,				
below mortar only, joints grouted with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete (1.4) with the work in vivid work in the concrete (1.4) with the work in vivid work in the concrete (1.4) with the work in vivid work in the concrete (1.4) with the work in vivid work in the concrete (1.4) with the work in vivid work i						
with admixture of white cement and colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete (1.4) with the work in visid increase.						
colouring pigment to match with colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete						
colour of tiles / epoxy grout materials of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete						
of approved make as directed and removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete (1.2.4) with the trans third translation of the surface of the surfa						
removal of wax coating of top surface of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete						
of tiles with warm water and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, (page76 staircase etc with cement concrete						
polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete (1.2.4) with the restriction process.		,				
cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete		of tiles with warm water and				
including the cost of materials, labour and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete (1:2.4) with the trans third in any staircase etc.		polishing the tiles using soft and dry				
and all other incidental charges complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete (1.2 A) with stars white Indian page 16		cloth upto mirror finish complete				
complete true to the manufacturer's specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete (1.2.4) with the part hid in part of the staircase etc.		including the cost of materials, labour				
specification and direction of Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete (1.2 cm) with the resolution of the cm with the concrete (1.2 cm)		and all other incidental charges				
Engineer-in-Charge. (White cement, synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete (1.2.2.4) with stone ships laid in panels.		complete true to the manufacturer's				
synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete		specification and direction of				
synthetic adhesive and grout material to be supplied by the contrr] With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete		Engineer-in-Charge. (White cement,				
With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete		synthetic adhesive and grout material				
With application slurry @1.75 kg/ Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete						
Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete		, , , ,				
Sq.m, 20 mm sand cement mortar (1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete		With application slurry @1.75 kg/				
(1:4) & 2 mm thick cement slurry at back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete						
back side of tiles, 0.2 kg/ Sq.m white cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, staircase etc with cement concrete						
cement for joint filling with pigment. Deep Colour & White 14. Artificial stone in floor, dado, (page76 staircase etc with cement concrete		* * *	Sqm.	45.00	1695.00	76275.00
Deep Colour & White 14. Artificial stone in floor, dado, (page76 staircase etc with cement concrete						
14. Artificial stone in floor, dado, (page76 staircase etc with cement concrete		, , , ,				
(page76 staircase etc with cement concrete	14.	·				
(4.2.4) with store shine leid in page 1						
I HATTIVIT I (E.I.) THEN SECTE CHIPS) ICIG III PONCIS						
as directed with topping made with	Item4)					
ordinary or white cement (as						
necessary) and marble dust in						
proportion (1:2) including smooth		• •				
proportion (1.2) morating smooth		proportion (1.2) merdaing smooth				

	finishing and rounding off corners including raking out joints or roughening of concrete surface and application of cement slurry before flooring works using cement @ 1.75 kg/sq.m all complete including all materials and labour. In ground floor. 3 mm. Thick topping (High polishing grinding on this item is not permitted with ordinary cement). Using grey cement 35 mm. Thick	Sqm.	45.00	330.00	14850.00
15.	Stripping off worn out plaster and raking out joints of walls, ceilings etc. Up to any height and in any floor including removing rubbish within a lead of 75m as directed.	Sqm.	20.00	19.00	380.00
16.	Plaster (to wall, floor, ceiling etc.) with sand and cement mortar including rounding off or chamfering corners as directed and raking out joints including throating, nosing and drip course, scaffolding/staging where necessary.[Excluding cost of chipping over concrete surface] With 1:6 cement mortar	Sqm.	20.00	203.00	4060.00
17.	25 mm thick plaster. Removal of rubbish,earth etc. From the working site and disposal of the same beyond the compound, in conformity with the Municipal / Corporation Rules for such disposal, loading into truck and cleaning the site in all respect as per direction of Engineer in charge.	Cum.	6.00	166.00	996.00
18. (page173 Item2)	Supplying, fitting and fixing boiling water proof ply conforming to IS: 710-1977 bonded with phenol formaldehyde synthetic resin conforming to IS: 848-1974 of approved make and brand fitted and fixed as per design as per approval and direction of Engineer-in-Charge. [excluding the cost of supporting frame work and teak wood batten/Lipping]. 6 mm th.	sqm	8.0	1122.00	8976.00
19.	Supplying fitting, fixing decorative lamination conforming to IS: 2046:				

	finish and thickness with fitting, fixing the same on Particle/MDF / Ply Boards with recommended / approved adhesive with proper clipping the sides for better attachment as per direction of Engineer-incharge.The rate includes the cost of labour, adhesive and all incidental charges thereof	Sqm.	8.0	802.00	6416.00
	Thickness of laminate 1.5mm				
20.	Supply of carpenter for dismantling the desk ,bench etc as directed	no	15.0	326.00	4890.00
21.	Hydraulic door closer of approved quality as per I.S.I. standard fitted and fixed complete.	no	2.0	1366.00	2732.00
22.	M.S. gate of Jail type as per approved design made of strong M.S. frame work, intermediate stiffeners and round / square bars or angles. M.S. sheet (not less than 14 gauge) gussets, cleats etc. including necessary riveting, bolting, welding, locking and hanging arrangements, fitting and fixing complete as per direction of the Engineer-in -charge. In ground floor.	Qtl.	2.00	7566.00	15132.00
(A) TOTAL-				F	S.387779.40

1995 as per approved make, brand,

(B) G.S.T @ 18% OF (A)------RS.69800.29

(C) TOTAL(A)+(B)------RS.457579.69

Name of the Agency

Address of the Agency

Rate quoted by the Agency

Signature of the Agency with date